

## 34DA - 34 Litre Aluminium Non - Refillable Cylinder

### Gas Contents

34 Litres

### Service Pressure

34 bar (500psi)

### Dimensions

Height 285 mm, Diameter 76 mm

### Weight

0.44 kg

### Cylinder Material & Valve

Aluminium - ISO or DOT approved connection C10 Valve (5/8"-18)

### Standards

NPL, UKAS or NIST standards. Manufactured gravimetrically to ISO 6142

### Equipment

- Cylinder valve compatible with all major manufacturer's regulators
- Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
- On-Demand flow regulator (for non-reactive, H<sub>2</sub>S and SO<sub>2</sub> mixtures)
- Variflow regulator (non-reactive gases)



### Warranty

Non-reactive gases	36 months
Ethanol	24 months
H <sub>2</sub> S, SO <sub>2</sub> and 4 gas mixtures	12 months
NO, NH <sub>3</sub> , HCN, ETO	12 months
Cl <sub>2</sub> (min 5ppm)	6 months
HCl (min 5ppm)	6 months
NO <sub>2</sub>	6 months

### Mixture Tolerances

Minor components are certified to the following analytical tolerance:

2 - 20ppm	= +/- 10%
21 - 50ppm	= +/- 5%
51 - 300ppm	= +/- 2%

### Specialty Gases and Gas Control Equipment

P.O. Box: 74582 Dubai, UAE Tel: + 971 4 3472436 Fax: +971 4 3472441

Email: [info@bristol-gases.com](mailto:info@bristol-gases.com), [www.bristol-gases.com](http://www.bristol-gases.com)